



otto

Wineemotion's OTTO dispensing system is designed to the standards demanded by commercial bars and restaurants with a clean, modern look simplifying the way wine is stored and served. Two independent zones allow for complete flexibility with a temperature range from 42°F to 70°F. Its sleek stainless-steel finish is not only elegant but durable, sanitary, and built to withstand the rigors of a high-traffic environment. Our commitment to using highest quality materials assures colder wine temperatures, hassle-free operations and years of trouble-free service.

PRODUCT FEATURES

❖ Temperature Range

- True Dual Zone: 42°F to 70°F for each 4-bottle zone.

❖ Refrigeration

- Dual evaporator and dual compressor enable maximum flexibility for wine storage of all varietals.
- Fan-forced front exhausting allows for easier built-in installations. Zero ventilation or drainage requirements.

❖ Usage Configuration

- Behind the Bar (for Staff Use).

❖ System Control

- Electronic key and dispensing lock activated by 4-digit PIN code.

❖ Portion Control

- 3 programmable portions from 0.5 to 9 oz.

❖ Preservation

- 30-Day Advanced Wine Preservation with Food Grade Argon or Nitrogen Gas (99.99% Purity).
- External Gas Tank Required.

❖ Display

- Central LCD display to access the technical menu.
- Energy saving feature with sleep mode and sensor wake-up.

❖ Doors

- Double pane, UV tinted thermal glass doors, the latest in energy efficient technology.

❖ Bottle Lifting System

- Manual gas spring pistons for fast and easy bottle changes.
- Ability to load any bottle size: 375mL to 750 mL.
- Fail-Safe functionality keeps bottles pressurized even when running out of gas.

❖ Lighting

- LED lighting to gently illuminate the labels.

❖ Finish

- Commercial-grade all stainless-steel interior and exterior provide superior durability and easy cleaning.
- Optional RAL Color Customization in Matte or Gloss Finish.

❖ ISOL-PLUS Technology

- Patented unique valve which prevents aromatic cross-contamination of wines in the same unit.

❖ AUTO-PUFF Valve

- Patented valve technology which automatically cleans the spout after each pour ensuring maximum freshness.

❖ OSHA Compliant

- ETL certified for safety (conforms to UL).
- ETL sanitation (conforms to NSF).

❖ Warranty

- Industry-leading 2-year warranty for owner's ease of mind.

Models	Width	Height	Depth	Weight	Electrical Requirements
OTTO Dual Temperature	39.69 in.	24.90 in.	15.67 in.	183 lbs	110VAC 60Hz – 2A